Bušilica pneumatska

1515



Profili

Atributi proizvoda

- dvosmjerna
- 1.800 o/min u slobodnom hodu
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 113 l/min
- priključak za zrak: 1/4"
- kapacitet glave: 1-10 mm
- navoj glave 3/8", 24 UNF
- unutarnji promjer cijevi: 10 mm

Prednosti:

- izuzetna snaga
- lagan, kompaktan alat kojim se jednostavno rukuje
- praktično pozicioniran prekidač
- ergonomski oblikovana drška za rad bez napora
- plastična zaštita drške za ublažavanje vibracija
- okretanje u oba smjera (lijevo/desno)
- brzostezna glava



	L	B	
617726	190	150	1360

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Upotreba (pictures)



Photo (pictures)



Accessories

 Spojnica muška

 Spojnica muška

 Spojnica ženska

 Spojnica ženska

 Pripremna grupa 3/8"

 Pripremna grupa 1/2"

 Crijevo spiralno za zrak

Safety tips

● The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.

● Regularly clean and dry the air filters and inlet air supply.

● Always use clean and dry air with the correct mixture of oil, for maximum tool life.

● Check the joints and ensure that the tubes and other equipment are not damaged before use.

● All tools should be gently oiled prior to being stored.

● Always store pneumatic tools in dry places away from water.

● Always use original spare parts.

● Repairs can be performed only by authorised staff people authorised by Unior d.d.

● Always disconnect tools not in use from the air supply.