

# Bušilica pneumatska

1515



## Profili




## Atributi proizvoda

- dvosmjerna
- 1.800 o/min u slobodnom hodu
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 113 l/min
- priključak za zrak: 1/4"
- kapacitet glave: 1-10 mm
- navoj glave 3/8", 24 UNF
- unutarnji promjer cijevi: 10 mm

## Prednosti:

- izuzetna snaga
- lagan, kompaktni alat kojim se jednostavno rukuje
- Praktično pozicioniran prekidač
- ergonomski oblikovana drška za rad bez napora
- plastična zaštita drške za ublažavanje vibracija
- okretanje u oba smjera (lijevo/desno)
- brzostezna glava



	<b>L</b>	<b>B</b>	
617726	190	150	1360

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## upotreba (pictures)



## Photo (pictures)



## Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Priprema grupa 3/8"



Priprema grupa 1/2"



Cijev spiralna za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.