

Brusilica kutna pneumatska

1517S



Profili



Atributi proizvoda


- broj okretaja u slobodnom hodu: 4500/min
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 340 l/min
- priključak za zrak: 1/4"
- navoj glave: 5/8"

Prednosti:

- lagan i kompaktan alat
- pogodno za ljevake i dešnjake
- zamjenjiva drška
- praktično pozicioniran prekidač

Upotreba:

- brušenje varova
- brušenje oštih rubova
- za manje neravne površine



617729

L

375

A

100

D

175



2610

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Upotreba (pictures)



Photo (pictures)



Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Priprema grupa 3/8"



Pripremna grupa 1/2"



Crijevo spiralno za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.