

Pneumatic angle sander

1517S



Profiles



Product features


- free speed 4500 revolution per minutes
- maximum air pressure: 6,2 Bar
- air consumption 340 l/min
- air inlet 1/4"
- spindle thread 5/8"

Advantages:

- small and compact tool
- suitable for lefthanders as well as for right-handers
- removable handle
- handy turn-on switch

Usage:

- grinding of welds
- grinding of sharp edges
- reparation of small uneven surfaces



617729

375

100

175

2610

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

Usage (pictures)



Photo (pictures)



Accessories




Coupling, male part



Coupling, male part



Coupling, female part



Coupling, female part



Pneumatic filter regulator and lubricator 3/8"



Pneumatic filter regulator and lubricator 1/2"



Spiral pneumatic hose

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.