

Brusilica pneumatska

1518



Profili



Atributi proizvoda

- broj okretaja u slobodnom hodu: 11000/min
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 170 l/min
- priključak za zrak: 1/4"


Prednosti:



- zamjenjiva drška
- sigurnosna ručica onemogućuje neželjeno uključivanje alata

Upotreba

- zaštita od rotirajućih dijelova

- može se koristiti u manjem prostoru
- industrija alata
- čišćenje varova
- čišćenje betonskih površina i zidova
- čišćenje drvenih površina
- odstranjivanje boja i lakova
- odstranjivanje hrđe
- rezanje profilnih nosača i lima
- druga kućna upotreba



	L	A	D	
617730	230	90	125	2175

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

upotreba (pictures)



Photo (pictures)



Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Cijev spiralna za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.