

Pneumatische staafslijper, haaks

1516A



Profielen



Product attributen


- free speed 20000 revolution per minutes
- maximum air pressure: 6,2 Bar
- air consumption 113 l/min
- air inlet 1/4"
- collet capacity 6 mm
- internal hose size 10mm

Voordelen:

- this angle edition enables access to difficult-to-reach places which normal grinders cannot reach
- safety lever which prevents accidental turn-on
- simple clamping of thin cut-off wheels (grinding/polishing pins) and other parts/ extensions
- extreme power based on size
- small and compact tool
- continuously variable regulation of rpm

Gebruik:

- precise grinding
- full grinding
- tool industry
- car industry
- aircraft industry
- cleaning of welds
- cleaning of concrete and wall surfaces
- cleaning of wooden surfaces
- removal of colours and varnish
- removal of rust
- grinding of bearings
- grinding of motor valves
- grinding of gears and coils
- various other surfaces



	L	А	1
617732	162	76	740

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Gebruik (Afbeeldingen)



Foto (Afbeeldingen)



Accessoires



🗯 Koppeling, man



🕨 Koppeling, vrouw



Koppeling, vrouw



Pneumatische filterdrukregelaar en olievernevelaar 3/8"



Pneumatische filterdrukregelaar en olievernevelaar 1/2"



Spiraalslang

Veiligheidstips



• The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.

• Regularly clean and dry the air filters and inlet air supply.

• Always use clean and dry air with the correct mixture of oil, for maximum tool life.

• Check the joints and ensure that the tubes and other equipment are not damaged before use.



• Always disconnect tools not in use from the air supply.

• All tools should be gently oiled prior to being stored.

• Always store pneumatic tools in dry places away from water.

• Always use original spare parts.

• Repairs can be performed only by authorised staff people authorised by Unior d.d.