# 1/2"冲击套筒

231/4 6p




## 配置文件

## 标准

ISO 2725 - 2

## 产品属性

- 材料：铬钼钢
- 落锻，完全淬火与回火
- 表面处理：根据DIN12476标准进行磷酸盐处理
- 根据ISO2725-2标准生产（只限公制规格）


## 优势：

- 6-point profile ensures optimal torque transfer while reducing the risk of rounding fasteners.
- Phosphate finish offers enhanced wear and corrosion resistance.

- Manufactured in accordance with ISO 2725-2 for dependable professional performance.

**用途:**

- Automotive and commercial vehicle maintenance.
- Use with pneumatic and cordless impact wrenches.
- Tightening and loosening fasteners on long threaded studs.
- Professional workshops, industrial maintenance, and repair operations




| | mm | D1 | D2 | L | T | |
|---|---|---|---|---|---|---|
| 603962 | 10 | 17.5 | 25 | 38 | 12 | 94 |
| 603963 | 11 | 18.7 | 25 | 38 | 12 | 95 |
| 603964 | 12 | 20 | 25 | 38 | 12 | 95 |
| 603965 | 13 | 21 | 25 | 38 | 12 | 96 |
| 603966 | 14 | 22.5 | 25 | 38 | 12 | 95 |
| 603967 | 15 | 23.7 | 30 | 38 | 12 | 140 |
| 603968 | 16 | 25 | 30 | 38 | 12 | 143 |
| 603969 | 17 | 26 | 30 | 38 | 13 | 140 |
| 609399 | 18 | 27.5 | 30 | 38 | 13 | 135 |
| 603970 | 19 | 28.7 | 30 | 38 | 13 | 132 |
| 603971 | 21 | 30 | 30 | 38 | 13 | 139 |
| 603972 | 22 | 32 | 30 | 38 | 13 | 133 |
| 603973 | 23 | 32 | 30 | 38 | 13 | 183 |
| 603974 | 24 | 35 | 30 | 45 | 20 | 179 |
| 603975 | 27 | 38.7 | 30 | 50 | 24 | 235 |
| 609400 | 28 | 40 | 30 | 50 | 24 | 255 |
| 603976 | 30 | 42 | 30 | 50 | 24 | 259 |

* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All

listed dimensions may vary in tolerance.

## Safety (pictures)

