

Ključ nasadni 3/4", impact, 6 kotni

232/4 6p



Profili



standard

ISO 2725-2

Atributi izdelka

- material: Premium Flex krom vanadijevo jeklo
- kovan, v celoti poboljšan
- površinska zaščita: fosfatiran po ISO 9717
- v celoti izdelan v skladu s standardom ISO 2725-2 (samo metrične dimenzije)
- v celoti izdelan v skladu s standardom DIN 3129



| Barcode | mm | D1 | D2 | L | T | Icon |
|---------|----|----|----|----|----|------|
| 603980 | 17 | 31 | 44 | 50 | 12 | 374 |
| 603981 | 19 | 33 | 44 | 50 | 13 | 387 |
| 603982 | 21 | 35 | 44 | 50 | 15 | 381 |
| 603983 | 22 | 37 | 44 | 50 | 15 | 400 |
| 603984 | 24 | 39 | 44 | 50 | 16 | 401 |
| 603985 | 27 | 43 | 44 | 54 | 19 | 410 |
| 609403 | 28 | 44 | 44 | 54 | 19 | 403 |
| 603986 | 30 | 47 | 44 | 54 | 21 | 438 |
| 603987 | 32 | 51 | 44 | 54 | 22 | 481 |
| 603988 | 33 | 51 | 44 | 54 | 22 | 497 |
| 603989 | 36 | 54 | 44 | 54 | 23 | 535 |
| 603990 | 41 | 60 | 44 | 58 | 27 | 634 |
| 603991 | 46 | 67 | 44 | 63 | 30 | 813 |

* Slike proizvodov so simbolične. Vse dimenzije so v mm, masa v g. Vse navedene dimenzije lahko odstopajo v tolerančnih merah.

Safety (slike)

