

Steckschlüssel 12-Kant 3/4 Zoll

197/1 12p




Profile



Produkteigenschaften

- Material: Premium Flex Chrom-Vanadium-Stahl
- geschmiedet, gehärtet und vergütet
- verchromt gemäß Industriestandard ISO 1456:2009
- poliert
- gefertigt laut Standard ISO 2725-1 (nur metrische Dim.)






D1

D2

L

T



		D1	D2	L	T	
618666	22	32.2	36	50	14	215
618667	23	33.2	36	50	14	216
618668	24	34.2	36	51	16	224
618669	26	37	36	52	16	220
618670	27	38	36	52	22	224
618671	28	39.5	36	52	22	234
618672	30	42	36	54	24	254
618673	32	44	36	56	26	282
618674	34	47	36	56	26	329
618675	36	50	38	58	28	372
618676	38	52	38	60	28	473
618677	41	56	40	64	30	487
618678	46	62	42	66	32	566
618679	50	68	42	70	34	683
618680	55	74	45	76	38	828
618681	60	80	45	78	42	993

* Bilder von Produkten sind Symbolfotos. Abmessungen sind in mm, Gewichte in Gramm.

Häufig gestellte Fragen

I attached the socket wrench to the pneumatic tool and the wall cracked. What could be wrong?

When working with pneumatic screwdrivers, you must use an impact socket wrench.