

Rezervne čeljusti za 721/6 i 722/6, aluminijske

722.1AL





Profili



Atributi proizvoda

- Materijal: aluminij
- Komplet od 2 komada

	В	1
623084	80	60
619026	125	156
619027	150	400
619029	200	541

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Safety tips

\checkmark

• Avoid clamping with heavy pressure on the corner of the vice jaws as it may break off a corner of a jaw.

• Replace a bent handle as soon as possible.

• Use bolts in all of the holes in the base of the vice.

• Use lock washers under the nuts.

• When work is held in a vice for sawing, saw as close to the jaws as possible to prevent vibrations. Be careful not to cut into the jaws.

• When clamping extra long work, support the far end of work rather than putting extra pressure on the vice.

• Regularly lightly oil all moving parts.

• If the threaded part of the vice is exposed, keep it free of chips and dirt.

• Discard any vice that exhibits the slightest hairline fracture.

• Always use a vice large enough to hold the work without strain.

\bigotimes

• Don't use the jaws of a vice as an anvil.

• Never use an extension handle for extra clamping pressure.

• Never pound on the handle to tighten beyond hand pressure.

- Never try to repair a vice by welding or brazing.
- Don't try to bend a heavy rod in a light vice.