

# Garnitura alata od 36 delova u SOS ulošku za alat

964/46SOS



## Profilii



## Opis proizvoda

- Dimenzije uloška 564x364x30 mm
- Odgovara fiokama kolica iz serija Eurostyle, Eurovision, Europlus i Hercules (sa prednjim fiokama)

## Sadržaj:

- 17 kom. dugih okasto-viljuškastih ključeva (art. 120/1), dim. 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24
- 9 kom. imbus ključeva na plastičnom držaču (art. 220/3), dim. 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm
- 6 kom. pljosnatih odvijača sa TBI ručkom (art. 605TBI), dim. 0.4x2.5x75, 0.5x3.0x80, 0.6x3.5x100, 0.8x4.0x100, 1.2x6.5x150, 1.2x8.0x175
- 2 kom. krstastih odvijača sa TBI ručkom (art. 615TBI), dim. PH 1x80, PH 2x100
- 1 kom. kratkog pljosnatog odvijača (art. 627TBI), dim. 1.0x5.5x25
- 1 kom. kratkog krstastog odvijača (art. 626TBI), dim. PH2x25

Naziv proizvoda	SKU	Artikal	Dimenzije	Količina
Garnitura alata od 36 delova u SOS ulošku za alat	623987	964/46SOS	-	36
Ključ viljuškasto-okasti dugi		120/1	6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24	17
Ključevi imbus na plastičnom držaču		220/3PH		1
Odvijač TBI pljosnati		605TBI	0.4 x 2.5x75, 0.5 x 3.0x80, 0.6 x 3.5x100, 0.8 x 4.0x100, 1.2 x 6.5x150, 1.2 x 8.0x175	6
Odvijač TBI krstasti PH		615TBI	PH 1x80, PH 2x100	2
Odvijač TBI pljosnati kratki		627TBI	1.0 x 5.5x25	1
Odvijač TBI krstasti PH kratki		626TBI	PH 2x25	1
SOS uložak za garnituru alata od 36 delova 964/46SOS		VL964/46SOS	564x364x30	1

\* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

## Pravilna upotreba



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

