Klešta kombinovana

406/1BI




Profili

Standardi

DIN ISO 5746

Opis proizvoda

- materijal: premium plus alatni čelik
- kovana, potpuno kaljena i ojačana
- rezne ivice induktivno kaljene
- čeljusti polirane
- površina hromirana ISO 1456:2009
- robusne ručke obložene dvokomponentnim navlakama
- utisnut logo UNIOR
- izrađena prema standardu ISO 5746




	L	B	C	A	
607870	160	24	35	9.5	224
607871	180	27	38	10	274
607872	200	29	41	10.5	341
608354	220	32	47	11	421

kapacitet sečenja (10N=1kg)

	L	max 1560 N/mm² ØT	max 750 N/mm² ØT
607870	160	1,6	2,0
607871	180	1,8	2,5
607872	200	2,0	2,5
608354	220	2,0	3,0

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Upotreba (slike)



Pravilna upotreba

- Pliers should be oiled regularly. A drop of oil at the hinge will lengthen the tool life and assure easy operation.

- Don't use pliers for cutting hardened wire, unless specifically manufactured for this purpose.
- Don't expose pliers to excessive heat. This may ruin the tool.

- When cutting wire with pliers, you should always wear glasses or goggles.
- Handles are provided for comfort. They are not intended to give user any degree of protection against electric shocks and should never be used on live electric circuits.
- Don't use pliers as a hammer.
- Don't hammer on the handles. They may crack or break.
- Don't extend the length of plier handles to secure greater leverage.
- Don't use pliers on nuts or bolts. A wrench will do a better job and with less risk of damage to the fastener.

Najčešće postavljana pitanja

Profil glave na vijku se do te mere deformisao da se ne može odvrnuti odvijačem. Koji UNIOR alat se može koristiti u ovom slučaju?
Klešta za vijke 407/4DP su najbolji izbor za odvrtanje vijaka sa oštećenim profilom glave.