

Dana të kombinuara

406/4G



Profiles







Standards

ISO 5746


Product features

- Materiali: çeliku të veçantë mjet
- rënie të falsifikuara, ngurtësuar tërësisht dhe nevrík
- prerja buzë induksion thekur
- Kreu Sipërfaqja përfundojë: finely toka
- përfundojë sipërfaqe: të veshura me fosfat me ISO 9717 standarde
- detyrë e rëndë plastike trajton
- bërë sipas standardit ISO 5746




	L	B	C	A		
608673	140	23	32	8	157	Till end of stock
608674	160	24	35	9.5	224	
608675	180	27	38	10	274	
608676	200	29	41	10.5	341	
608677	220	32	47	11	421	

Kapaciteti i prerjes (10N = 1 kg)

	L	max 1560 N/mm ² Ø↑	max 750 N/mm ² Ø↑
608673	140	1,6	2,0
608674	160	1,6	2,0
608675	180	1,8	2,5
608676	200	2,0	2,5
608677	220	2,0	3,0

* Imazhet e produkteve janë simbolike. Të gjitha dimensionet janë në mm, pesha në gram. Të gjitha dimensionet e listuara mund të ndryshojnë në tolerancë.

Usage (pictures)



Frequently asked questions

The head profile on the screw has deformed to such an extent that it cannot be unscrewed with a screwdriver. Which Unior tool can be used in this case?

407/4DP screw pliers are the best choice for unscrewing screws with a damaged head profile.