

# 多功能斜嘴钳

462/1VDEBI



## 配置文件




## 产品属性

- 材料：特种工具钢
- 落锻，完全淬火与回火
- 切削刃感应淬火
- 头部抛光
- 表面处理：依据ISO 1456:2009进行镀铬处理
- 重型双成分材料手柄
- 根据EN IEC 60900标准生产

## 优势：

- 剥离横截面积为1.5mm<sup>2</sup>和2.5mm<sup>2</sup>的导线绝缘层





L

B

A

C



624060

160

21

10

22

214

cutting capacity



L

max 1600 N/mm<sup>2</sup> Ø↑max 650 N/mm<sup>2</sup> Ø↑

624060

160

1,6

2,5

\* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

## Frequently asked questions

### **Are certified insulated tools made through a different procedure than non-certified insulated tools?**

The tools are made according to the same procedure.

### **Are insulated (VDE) tools considered as personal protective equipment (PPE)?**

According to EU regulations, VDE tools are not considered as PPE.

### **Is it possible to work with insulated pliers under electrical voltage?**

Yes, but only by professionals who follow safety requirements and use additional personal protective equipment.

### **Are the VDE tools only being sampled in series production?**

The high voltage test (at 10kV) is performed fully on each tool. Other tests are performed in accordance with the EN60900 standard.