

VDE TBI 绝缘细长电工螺丝刀



配置文件



标准

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

产品属性

- 螺丝刀:切割器 特种工具钢、锻造、完全淬火与回火,完全淬火与回火
- 黑色刀头
- 手柄:符合人体工程学的形状
- 三种成分组成的材料
- 挂孔
- 根据DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018标准生产

优势:

- 带细长刀片的型号
- 尽管螺丝刀形状细长,其作为正常绝缘螺丝刀时,功能和安全性与普通螺丝刀一致。
- 细长的刀片可以对难以触及的位置进行作业



	axb	С	L	ů
624063	0.6 x 3.5	100	185	37
624064	0.8 × 4.0	100	185	39
624065	1.0 x 5.5	125	225	74

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

用途 (pictures)





Safety tips



 Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.

• Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.

• A rounded tip should be redressed with a file; make sure edges are straight.

 Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.

• Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.

• A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade



• Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.

 Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.

• Don't use a screwdriver with a split or broken handle.

 Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

 Don't use tools that shows sign of wear and have the second layer of plastic visible.

might break and send a particle of steel into the operator's arm or even towards his eyes.

• VDE tools that have several parts, have to be assembled correctly before use.

• When working with VDE tools avoid contact with water.