

Pinza a becchi lunghi con tagliante laterale

506/1BI



Profili



Standard

DIN ISO 5745

Attributi del prodotto

- materiale: acciaio al carbonio plus premium
- interamente bonificato
- bordi di taglio induriti a induzione
- teste lucidate
- finitura superficiale: cromata ISO 1456:2009
- robusta impugnatura bicomponente
- superficie di presa zigrinata
- conforme allo standard ISO 5745
- anche per stringere e separare cavi e altri oggetti sensibili



| | L | B | D | A | C | |
|--------|-----|----|-----|---|----|-----|
| 607874 | 140 | 15 | 2 | 8 | 39 | 115 |
| 607875 | 160 | 16 | 2.5 | 9 | 49 | 137 |

capacità di taglio (10N=1kg)

| | L | max 1560 N/mm ² Ø↑ | max 750 N/mm ² Ø↑ |
|--------|-----|-------------------------------|------------------------------|
| 607874 | 140 | 1,6 | 2,0 |
| 607875 | 160 | 1,6 | 2,0 |

* Le immagini dei prodotti sono puramente simboliche. Tutte le dimensioni sono in mm, peso in grammi.

Photo (pictures)



Frequently asked questions

The head profile on the screw has deformed to such an extent that it cannot be unscrewed with a screwdriver. Which Unior tool can be used in this case?

407/4DP screw pliers are the best choice for unscrewing screws with a damaged head profile.