

Yan keskili kargaburun penseler

506/1BI



Profiles




Standards

DIN ISO 5745

Product features

- malzeme: özel alet çeliği
- sıcak dövme, tamamen sertleştirilmiş ve temperlenmiş
- kesici ağızlı endüksiyonla sertleştirilmiş
- başlık cilalıdır
- yüzey bitirme: ISO 1456:2009 standardına göre krom kaplamalı
- ağır hizmet tipi iki bileşenli saplar
- kavrama yüzeyi tırtıllıdır
- ISO 5745 standardına göre yapılmıştır
- ayrıca sıkıca tutmak ve kablolardan ve diğer hassas nesnelere ayırmak için kullanılır



Barcode	L	B	D	A	C	Weight
607874	140	15	2	8	39	115
607875	160	16	2.5	9	49	137

kesme kapasitesi (10N=1kg)

Barcode	L	max 1600 N/mm ² Ø↑	max 650 N/mm ² Ø↑
607874	140	1,6	2,0
607875	160	1,6	2,0

* Ürünlerin resimleri semboliktir. Bütün boyutlar mm ve ağırlık gram cinsindedir.

Photo (pictures)



Frequently asked questions

The head profile on the screw has deformed to such an extent that it cannot be unscrewed with a screwdriver. Which Unior tool can be used in this case?

407/4DP screw pliers are the best choice for unscrewing screws with a damaged head profile.