

# Dana anësore të forta për prerje

466/1BI



## Profiles




## Standards

DIN ISO 5749

## Product features

- Materiali: çeliku të veçantë mjet
- rënje të falsifikuara, ngurtësuar tërësisht dhe nevrik
- prerja buzë induksion thekur
- kreu i lëmuar
- përfundojë sipërfaqe: krom kromuar për ISO 1456:2009 standarde
- të rënda në detyrë të dyfishtë - komponent trajton
- bërë sipas standardit ISO 5749





L

B

A

C



608850	180	28	11	20	313
608837	200	27	11	21	344

Kapaciteti i prerjes (10N = 1 kg)

L	max 2150 N/mm <sup>2</sup> Ø†	max 750 N/mm <sup>2</sup> Ø†
608850	180	1,8
608837	200	2,0

\* Imazhet e produkteve janë simbolike. Të gjitha dimensionet janë në mm, pesha në gram.Të gjitha dimensionet e listuara mund të ndryshojnë në tolerancë.

## Frequently asked questions

### **What does it mean that the pliers are quenched and tempered and the head parts/teeth of the pliers are inductively hardened?**

It means that the pliers are thermally processed by quenching and tempering their entire surface to a hardness of about 45HRc, while head parts are additionally inductively hardened to a hardness of at least 60HRc.

### **What is meant by the statement that pliers are made in accordance with the stated ISO standard?**

It means that the pliers are in accordance with the international standard in terms of dimensions, strength and structure, and compliance is determined by prescribed tests.