Kliješta za sječenje žice, kosa, robusna

466/1BI




Profili

Zatvori pretraživanje

DIN ISO 5749

Atributi proizvoda

- materijal: Premium Flex Plus poseban alatni čelik
- kovana, potpuno poboljšana i ojačana
- rezni rubovi induktivno kaljeni
- čeljusti polirane
- završna obrada: kromiranje po standardu ISO 1456:2009
- robusne ručke izolirane dvokomponentnim navlakama
- izrađeno po standardu ISO5749



	L	B	A	C	
608850	180	28	11	20	313
608837	200	27	11	21	344

sposobnost rezanja (10K=1kg)

	L	max 2150 N/mm² Ø	max 750 N/mm² Ø
608850	180	1,8	3,0
608837	200	2,0	3,5

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Frequently asked questions

What does it mean that the pliers are quenched and tempered and the head parts/teeth of the pliers are inductively hardened?
It means that the pliers are thermally processed by quenching and tempering their entire surface to a hardness of about 45HRc, while head parts are additionally inductively hardened to a hardness of at least 60HRc.

What is meant by the statement that pliers are made in accordance with the stated ISO standard?
It means that the pliers are in accordance with the international standard in terms of dimensions, strength and structure, and compliance is determined by prescribed tests.