

Ađır hizmet tipi yan keskiler

466/1BI



Profiles






Standards

DIN ISO 5749


Product features

- malzeme: özel alet çeliđi
- sıcak dövme, tamamen sertleştirilmiş ve temperlenmiş
- kesici ağızlı endüksiyonla sertleştirilmiş
- başlık cilalıdır
- yüzey bitirme: ISO 1456:2009 standardına göre krom kaplamalı
- ağır hizmet tipi iki bileşenli saplar
- ISO 5749 standardına göre yapılmıştır



	L	B	A	C	
608850	180	28	11	20	313
608837	200	27	11	21	344

kesme kapasitesi (10N=1kg)

	L	max 2150 N/mm ² Ø↑	max 750 N/mm ² Ø↑
608850	180	1,8	3,0
608837	200	2,0	3,5

* Ürünlerin resimleri semboliktir. Bütün boyutlar mm ve ağırlık gram cinsindedir.

Frequently asked questions

What does it mean that the pliers are quenched and tempered and the head parts/teeth of the pliers are inductively hardened?

It means that the pliers are thermally processed by quenching and tempering their entire surface to a hardness of about 45HRc, while head parts are additionally inductively hardened to a hardness of at least 60HRc.

What is meant by the statement that pliers are made in accordance with the stated ISO standard?

It means that the pliers are in accordance with the international standard in terms of dimensions, strength and structure, and compliance is determined by prescribed tests.