

# Ključ moment, nastavljivi

263



## Profili

---



## Atributi proizvoda

- Točnost: +/-3%
- Mikro skala za jednostavno podešavanje bez grešaka
- Mogućnost fiksiranja željenog momenta
- Brzo podešavanje - dovoljno je osam (8) okretaja da se pokrije cijela skala
- Djelovanje okretnog momenta: u oba smjera, ali uvijek koristite smjer koji je trenutno podešen na dršci moment ključa
- Materijal ručke: dvokomponentni materijal
- Dvojna skala: lbf.ft i Nm
- Dodatni stalak za pohranu alata pomaže da se ključ otkoči i podesi željeni obrtni moment.
- radni ugao: 5°

## Warranty

- 1 year warranty
- Extend warranty for your product (<https://uniortools.com/eng/support/product-registration>)

## Važno!

- Moment ključ ne koristite za odvijanje!
- Moment ključ vrši pritezanje samo u smjeru prikazanom na naljepnici ključa. Naljepnica označava ispravan smjer pritezanja!

- Predviđeni period za recalibraciju moment ključa je 12 mjeseci ili približno 5.000 mjerenja od dana kupnje
- Nakon mjerenja UVIJEK podesite mjerni mehanizam na početnu poziciju.
- Kada postignete željeni moment, odmah prestanite sa stezanjem
- Moment ključ se u slučaju nepridržavanja uputa za upotrebu može oštetiti



626765	3/8"	12 - 60	10 - 45	328	700
626766	1/2"	40 - 200	30 - 150	459	1000
626767	1/2"	60 - 340	50 - 250	679	1550

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

### upotreba (pictures)



### Photo (pictures)



## Safety tips



- Only an authorised person in a certificated service centre can perform technical maintenance.
- Tools should always be serviced and calibrated by a certified service engineer.
- Tool should only be used for precise tightening as specified in the instruction manual.
- Check instruction manual on how to read the value scale on the tool properly.
- Stop tightening after hearing a feedback from the tool.
- Use only sockets with the same square drive.
- Always return the value on the scale back to 0 after usage and before storing.

## Safety (pictures)

