

전공 절연 토크 렌치

266



프로파일



제품 특징

- target torque warning: buzzer + 12 LED lights
- 작동 모드: 홀드(hold)/트랙(track)
- 단위 선택: N-m, in-lb, ft-lb, kg-cm
- head type: interchangeable head
- gear teeth: 52
- battery: AA × 2 pcs (not included)
- battery life (continuous operation): 110 hrs.
- battery life (standby): 1 year

data memory size: 250 inputs

9 preset toque settings

operating temperature: -10°C ~ 60°C

storage temperature: -20°C ~ 70°C

humidity: up to 90 % non-condensing

drop test: 1 m

vibration test: 10G

electromagnetic compatibility certificate

accuracy CW: +/-2%, CCW: +/-3%

PC connectivity

Download data transfer program
 (https://www.uniortools.com/res/files/assets/Uploads/266_calibration_program.zip)

Warranty

● 워런티: 10.000 사이클/1년



		(Nm)	L	axb	ů
627575	1/4"	1,5 - 30	390	9 x 12	1395
627576	1/2"	6,8 - 135	410	9 x 12	1619
627577	1/2"	10 - 200	545	14 x 18	2268

^{*} Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

사용법 (사진)







사진 (사진)







액세서리



Ratchet insert tool for 266



Adjustable wrench insert tool for 266



Open ring insert tool for 266

안전 수칙





- 인증된 서비스 센터에서 승인된 사람만 기술 유 지 보수를 수행할 수 있습니다.
- 공구는 항상 인증된 서비스 엔지니어가 서비스 하고 보정해야 합니다.
- 공구는 사용 설명서에 명시된 대로 정밀하게 조 일 때만 사용해야 합니다.
- 공구의 값 눈금을 올바르게 읽는 방법은 사용 설명서를 확인하십시오.
- 공구의 피드백이 들리면 조임을 중지하십시오.
- 동일한 정사각형 드라이브의 소켓만 사용하십 시오.
- 사용 후 또는 보관하기 전에 항상 측정 값을 0으로 되돌리십시오.

안전 (사진)







