

uzatma kolu 1/2", yüksekliklerde güvenli çalışma için

190.4/1-H



Profiles



Product features

- malzeme: krom vanadyum
- sıcak dövme, tamamen sertleştirilmiş ve temperlenmiş
- yüzey bitirme: ISO 1456:2009 standardına göre krom kaplamalı
- cilalı başlık
- ISO 3315-B (aksesuarlar) ve ISO 2725-1B (soketler) standartlarına uygun olarak üretilmiştir

Avantajları:

- takım ağırlığı her takımın üzerinde işaretlenmiştir
- Prizlerin ve aksesuarların değiştirilmesi özel bir alet kullanılmasını gerektirir (Madde 1111)
- Yan delikli prizler ve aksesuarlar

Dikkat!

- Anahtar prizleri ve aksesuarlar önceden güvenli veya emniyetli bir alanda yapılmalıdır.



626103



1/2"

L

125

D1

16,8

D2

24



183



L

D1

D2



626104

1/2"

250

16,8

24

331

* Ürünlerin resimleri semboliktir. Bütün boyutlar mm ve ağırlık gram cinsindedir.

Usage (pictures)



The carabiner on the lanyard is attached to the ring on the tool. The rings on the tools are large enough to accept 2 carabiners.



The carabiner on the lanyard has to be protected against opening using a lock ring.



Before removing the tool from the belt, unscrew the lock ring on the carabiner on the belt.



Open the carabiner on the belt and remove the tool, which is attached to a lanyard, from the carabiner on the belt. The tool is now ready for use.



Correct attachment of the tool to the lanyard. Return the tool to the belt following the steps in reverse order.



Using the socket remover (Article 1111) depress the pin in the hole while removing the socket from the square drive of the ratchet and then switch the socket or extension.

Safety tips



- Always change tools in secure areas where there is no risk of falling tools.
- Always use tools with Unior carabiners and never use carabiners with a diameter less than 6mm.
- Tools being used at height should regularly be checked for damage and that there is no damage to lanyards, carabiners, attachment rings or belts.



- Don't use tools without attaching them to your work belt when working at height.
- Don't use and fix damaged tools.
- Don't exceed maximum weight of 2.3kg for individual tools that a worker can attach to their belt.

Safety (pictures)



Frequently asked questions

Can we use a tool for working at height as a normal tool?

A tool for working at height has the same usability as a normal tool, except that a non-removable riveted metal buckle is added to this tool.

Does the stated weight per tool for safe work at height also include the weight of the metal ring?

The weight of the tool marked on the tool, included also weight of metal ring