


# Kliješta seger, vanjska, ravna, za siguran rad na visini

532/1P-H



## Profili

---



## Atributi proizvoda

- Kako bi se osiguralo najviši stepen sigurnosti, pričvrсна kopča nije samo umetnuta kroz plastični rukavac već i kroz osnovni materijal - kliješta
- zakovica metalne kopče koja se ne može demontirati
- materijal: Premium Plus specijalni alatni čelik
- kovana, potpuno poboljšana i ojačana
- čeljusti polirane
- površina kromirana ISO 1456:2009
- vrhovi brunirani
- ručke izolirane plastičnom masom
- izrađena prema standardu DIN 5254 oblik A


## Prednosti:

- na svakom je alatu označena težina alata
- dvije kopče mogu se učvrstiti u kopču, što osigurava sigurnu promjenu alata

- Unior je prilagođen za rad na visini i održava osnovne funkcije alata
- 30% veća izdržljivost u usporedbi sa običnim kliještima za seger
- sa ojačanim vrhovima
- za promjere od 10 do 100 mm

## Upotreba:

- za montažu seger prstenova na osovinu




	<b>L</b>		<b>D</b>	<b>C</b>	
626386	180	19 - 60	1,8	52	205

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## Upotreba (pictures)



The carabiner on the lanyard is attached to the ring on the tool. The rings on the tools are large enough to accept 2 carabiners.



The carabiner on the lanyard has to be protected against opening using a lock ring.



Before removing the tool from the belt, unscrew the lock ring on the carabiner on the belt.



Open the carabiner on the belt and remove the tool, which is attached to a lanyard, from the carabiner on the belt. The tool is now ready for use.



Correct attachment of the tool to the lanyard. Return the tool to the belt following the steps in reverse order.



Using the socket remover (Article 1111) depress the pin in the hole while removing the socket from the square drive of the ratchet and then switch the socket or extension.

## Safety tips



- Always change tools in secure areas where there is no risk of falling tools.
- Always use tools with Unior carabiners and never use carabiners with a diameter less than 6mm.
- Tools being used at height should regularly be checked for damage and that there is no damage to lanyards, carabiners, attachment rings or belts.



- Don't use tools without attaching them to your work belt when working at height.
- Don't use and fix damaged tools.
- Don't exceed maximum weight of 2.3kg for individual tools that a worker can attach to their belt.

## Safety (pictures)



## Frequently asked questions

### Can we use a tool for working at height as a normal tool?

A tool for working at height has the same usability as a normal tool, except that a non-removable riveted metal buckle is added to this tool.

**Does the stated weight per tool for safe work at height also include the weight of the metal ring?**

The weight of the tool marked on the tool, included also weight of metal ring