# Čekić za kamen, macola, za siguran rad na visini

817-H




## Profili

## Atributi proizvoda

- Materijal: Premium Flex Plus alatni čelik
- Kovan
- Udarna površina induktivno kaljena

## Prednosti:

- kovana metalna kopča koja se ne može rastaviti
- na svakom je alatu označena težina alata
- u kopču je moguće učvrstiti dva karabina, što omogućuje sigurnu zamjenu alata
- Alat Unior je prilagođen radu na visini i održava osnovne funkcije alata
- Ergonomska gumirana ručka apsorbira udarce i vibracije, što olakšava uporabu.
- Poseban proces kod pričvršćivanja glave omogućava da ostane fiksirana na ručki.
- Ručku odlikuje iznimna izdržljivost, jer su po dužini postavljene 4 opruge čelične trake. Vrpce su pričvršćene na glavu čekića, čime se osigurava dodatna sigurnost kod korištenja.




| | gr | A | L | |
|---|---|---|---|---|
| 627542 | 1800 | 40 | 300 | 2356 |

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## upotreba (pictures)



Pričvrstite karabiner na remenu za vezivanje na kopču alata. Kopče su dovoljno velike da drže 2 karabinera.



Karabiner se mora osigurati od otvaranja zatezanjem matice.



Prije skidanja alata s remena, odvrnite maticu na karabineru.



Otkopčajte karabiner na remenu i uklonite alat pričvršćen za uzicu. Alat je sada spreman za rad.



Na slici je prikazan pravilno pričvršćen alat na remenu za vezivanje s kojim koristimo alat.



Pritisnite iglu u rupu s alatom za rastavljanje nasadnog ključa (stavka 1111), te istovremeno uklonite nasadni ključ sa račne i zamijenite nasadni ključ ili nastavak.

## Safety tips

- Always change tools in secure areas where there is no risk of falling tools.
- Always use tools with Unior carabiners and never use carabiners with a diameter less than 6mm.
- Tools being used at height should regularly be checked for damage and that

- Don't use tools without attaching them to your work belt when working at height.
- Don't use and fix damaged tools.
- Don't exceed maximum weight of 2.3kg for individual tools that a worker can attach to their belt.

there is no damage to lanyards,
carabiners, attachment rings or belts.

## Safety (pictures)




## Frequently asked questions

**Can we use a tool for working at height as a normal tool?**
A tool for working at height has the same usability as a normal tool, except that a non-removable riveted metal buckle is added to this tool.

**Does the stated weight per tool for safe work at height also include the weight of the metal ring?**
The weight of the tool marked on the tool, included also weight of metal ring