气动扳手

1566



配置文件

1year extended warranty 1/2"

产品属性

- 每分钟8000转的空载转速
- 最大扭矩值1223 Nm
- .
- 推荐气压:6.2Bar
- 空气消耗量113 升/分钟
- 1/4"进气口
- 噪音级93db (A)
- 最大螺栓尺寸M24

优势：

- 复合外壳
- 机械双锤
- 单手操作 前进/后退
- 紧凑和强大的
- 变速触发

用途:

- 汽车行业
- 航空业
- 农业设备
- 重工业
- 大型建筑机械
- 造船业
- 单独安装

重要事项！

- 务必使用Unior气动套筒

		L	A	B	Nm	
627570	1/2"	187	70	193	1223	2227

* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All listed dimensions may vary in tolerance.

用途 (pictures)








Photo (pictures)



Accessories


气动管接头


气动管接头


气动管接头


气动管接头


3/8"气动过滤调节器和润滑器


1/2"气动过滤调节器和润滑器



螺旋气动软管

Safety tips

● The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.

● Regularly clean and dry the air filters and inlet air supply.

● Always use clean and dry air with the correct mixture of oil, for maximum tool life.

● Check the joints and ensure that the tubes and other equipment are not damaged before use.

● All tools should be gently oiled prior to being stored.

● Always store pneumatic tools in dry places away from water.

● Always use original spare parts.

● Repairs can be performed only by authorised staff people authorised by Unior d.d.

● Always disconnect tools not in use from the air supply.