

Izvijač pneumatski, kompozitni, prihvat 3/4"

1573



Profili



Atributi proizvoda

- 5.500 o/min u slobodnom hodu
- max. obrtni momenat 2034 Nm
- .
- preporučeni pritisak vazduha: 6, 2 bara
- potrošnja vazduha 198 l / min
- priključak za zrak: 3/8"

- nivo buke 93 dB (A)
- za vijke do M30

Prednosti:


- kompozitno kućište motora
- Dvojni udarni mehanizam TwinHammer
- jednu ruku napred / nazad
- kompaktan i moćan
- Obarač brzine








Upotreba:

- automobilska industrija
- avionska industrija
- poljoprivredna mehanizacija
- teška industrija
- veći građevinski strojevi
- brodogradnja
- individualna montaža

Važno!

- **UVIJEK** koristite Uniorove IMPACT nasadne ključeve i pribor



| | | | | | | |
|--|---|---|---|---|---|---|
|  |  |  |  |  |  |  |
| 627571 | 3/4" | 220 | 88 | 217 | 2034 | 3764 |

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Upotreba (pictures)



Photo (pictures)



Accessories



Spojnica muška



Spojnica ženska



Priprema grupa 3/4"



Crijervo spiralno za zrak

Safety tips



● The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.



● Always disconnect tools not in use from the air supply.

- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.