

Izvijač pneumatski, prihvatač 3/4"

1573



Profili



Atributi proizvoda

- 5.500 o/min u slobodnom hodu
- Max. okretni momenat 2034 Nm
- .
- Preporučeni radni tlak: 6, 2 bara
- Potrošnja zraka 198 l / min
- Priključak za zrak: 3/8"
- Razina buke 93 dB (A)
- za vijke do M30

Prednosti:


- Kompozitno kućište motora
- Dvojni udarni mehanizam TwinHammer
- Jednoručna izmjena smjera rada
- Kompaktan i moćan
- Obrača brzine





Upotreba

- Automobilaska industrija
- Avionska industrija
- Poljoprivredna mehanizacija
- Teška industrija
- Veći građevinski strojevi
- Brodogradnja
- Individualna montaža

Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



		L	A	B		
627571	3/4"	220	88	217	2034	3764

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

upotreba (pictures)



Photo (pictures)



Accessories



Spojnicica muška



Spojnicica ženska



Priprema grupa 3/4"



Cijev spiralna za zrak

Safety tips



● The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.



● Always disconnect tools not in use from the air supply.

- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.