

# Slagmoersleutel 3/4"

1573



## Profielen



## Product attributen

- free speed 5500 revolution per minutes
- max. torque 2034 Nm
- .
- recommended air pressure: 6,2 Bar
- air consumption 198 l/min
- air inlet 3/8"
- noise level 93 dB(A)
- max bolt size M30

## Voordelen:


- composite motor housing
- twin hammer mechanism
- one hand forward / reverse
- compact and powerful
- variable speed trigger





## Gebruik:

- car industry
- aircraft industry
- agricultural equipment
- heavy industry
- larger construction machinery
- shipbuilding industry
- individual mounting

## Important!

- Always use Unior IMPACT sockets.



		<b>L</b>	<b>A</b>	<b>B</b>		
627571	3/4"	220	88	217	2034	3764

\* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

## Gebruik (Afbeeldingen)



## Foto (Afbeeldingen)



## Accessoires



Koppeling, man



Koppeling, vrouw



Pneumatische filterdrukregelaar en olieverniveelaar 3/4"



Spiraalslang

## Veiligheidstips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.



- Always disconnect tools not in use from the air supply.

- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.