


Boutenschaar BOLTSHARK

469SHARK/4AP



Profielen



Standaard

DIN ISO 5743


Product attributen

- These ultra-powerful cutters are used to easily cut metal wire, including hardened and tempered alloys, and other extruded metals. They are ergonomically designed to apply a maximum force, while being easy on the hands. Drop-forged from Premium Hard Plus carbon steel with induction hardened cutting edges, BoltShark cutter can cut through up to 6mm of soft metal wire, 4mm of hard steel, and 3.6mm of tempered piano wire or steel spring. In addition to wire, the Boltshark cutters will quickly and cleanly cut through 5mm diameter nails, screws and rivets.
- drop forged from Premium Hard Plus carbon steel
- fully hardened to ~47HRc, with cutting edges induction hardened to ~64HRc
- finished with an anti-corrosive black coating and lightly oiled
- double-dipped plastic non-slip handles provide good ergonomic hand grip

Voordelen:

- Engineered with a two-rivet joint, which uses a compound action to give increased cutting force with less effort.

- The strongest force needs to be applied at the start of the cut, when the handles are furthest apart. BoltShark cutters are designed with the handles tighter together allowing the maximum force to be applied from the very start of the cut.
- Central cutting edges leave a bevelled finish on both sides of the cut.
- for precise cutting of soft (up to 6 mm), hard (up to 3,5 mm) and piano wires (up to 3 mm)
- easily cuts parts such as screws, nails, rivets, etc. up to 4 mm thickness



	L	B	A	C	
627533	200	34,8	19,5	16,5	354

knipcapaciteit (10N=1kg)


	L	max 2150 N/mm ² Ø↑	max 1600 N/mm ² Ø↑	max 650 N/mm ² Ø↑
627533	200	3	3,5	6

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Gebruik (Afbeeldingen)



Foto (Afbeeldingen)



Veelgestelde vragen

Do the names Shark and Boltshark mean anything?

These names describe the principles behind operating the cutting pliers.

Wat betekent het dat de tang gehard en getemperd is en dat de kopdelen/tanden van de tang inductief gehard zijn?

Dit houdt in dat de tangen thermisch worden bewerkt door het gehele oppervlak af te schrikken en te temperen tot een hardheid van ongeveer 45HRc, terwijl de kopdelen bovendien inductief worden gehard tot een hardheid van minimaal 60HRc.

Wat wordt bedoeld met de opgave dat tangen zijn gemaakt volgens de gestelde ISO-norm?

Het betekent dat de tang qua afmetingen, sterkte en structuur voldoet aan de internationale norm en dat de conformiteit wordt bepaald door voorgeschreven tests.