

Tavolinë kontrollë mobile për dokumente me panel për vegla

994W




Profiles



Product features

Kjo tavolinë e lëvizshme, me shumë qëllime, e qëndrueshme dhe e sigurt me shpinë të shpuar ju jep mundësinë të shkurtoni lëvizjet tuaja gjatë procesit të punës. Ai siguron një hapësirë pune të rregullt, akses në burime, mjete bazë dhe dokumentacion. Mbrapa e shpuar lejon që të varen elementë shtesë, të cilët ofrojnë mundësi shtesë dhe dukshmëri të shtuar. Sipërfaqja e punës është e mjaftueshme për punë të qetë dhe gjërat mbyllën kur nevojitet. Është e nevojshme në punishte, magazina dhe kudo brenda Sistemit të prodhimit efikas.

- Materiali: fletë metalike
- sipërfaqja e punës është e qëndrueshme, pllaka bartese me dimension A3 e fiksuar me nje kapse per ta shternguar letren
- skajet e ngritura parandalojnë rënien e letrës dhe dokumentacionit dhe i mbajnë ato në tabelë
- mbajtëse e telefonit celular
- hapsira për ruajtjen e lapsave
- Sipërfaqe "e zhytur" për ruajtjen e aksesorëve
- 2 sirtarë L 563 x F 365 x Lartë 70 mm
- sirtarët mund të ndahen dhe rregullohen me grup ndarjesh 940ES3A ose 940ES3
- 2 ndarje për ruajtje në pjesën e poshtme të tavolinës së lëvizshme
- dorezë ergonomike
- dimensionet bazë me dorezë dhe rrota L 770 x W 460 x H 1669 mm
- Sistemi mbyllje
- 4 rrota, një me frena
- tabaka me krye, gjashtë kalemata;
- mbulon sintetike mbrojtur mbathje dhe mjetet nga dëmtimi
- të veshura me ngjyra ekologjike, me kadmium dhe të çojë falas
- Kapaciteti maksimal i çdo sirtar: 45 kg
- sirtarët janë të pajtueshëm me të 3 madhësitë e futjeve SOS: 1/3, 2/3, 3/3
- pllakë me vrima për ruajtjen e veglave (përforimi standard Unior)



| | | | | | | | | |
|--|-----|-----|-------|-----|------|------|------|---|
|  | L | L1 | B | B1 | H | H1 | H2 |  |
| 628371 | 770 | 673 | 460.5 | 440 | 1669 | 1125 | 1252 | 45000 |

* Imazhet e produkteve janë simbolike. Të gjitha dimensionet janë në mm, pesha në gram. Të gjitha dimensionet e listuara mund të ndryshojnë në tolerancë.

Accessories




Dera për 994

Spare parts



Lock with keys



Rrëshqitje top-duke 940E1-9



Set of casters

Safety tips



- Lock all your drawers before trying to roll the tool carriage into a new work area.
- Set the brakes on the locking casters after you have rolled the cabinet to your work area.
- Treat you tool carriage, tool chests, or tool boxes with respect.
- Always follow the prescribed max load capacity of individual drawers and the carriage as a whole.
- Always put heavier objects in the bottom drawers
- Always close drawers when not in use.
- Always follow manufacturer manual instructions regarding assembly and repair of your tools.



- Don't open two or more drawers at the same time, there is high chance of it tipping over.
- Don't throw tools into drawer, always put the tools in.
- Don't use an opened drawer as a working surface.
- Don't clean a lacquered surface with a solvent cleaner.
- Don't pull a tool carriage as you won't be able to see where you are headed. Push it in front of you so you can see where you are going.
- Don't stack a tool carriage with too many extra chests or tool trays; it may tip over at the most unexpected time.
- Don't roll a tool carriage with loose tools or parts on top of the carriage.
- Don't roll a tool carriage too quickly; a pot hole in the floor or some hardware on the floor may cause an accident.
- Don't overload the drawers; if you haven't got room for all of your tools, you need a larger tool carriage.
- Don't open up too many loaded drawers at a time; close each drawer before opening up

another. Heavily loaded opened drawers are an invitation to tipping.