

# Stand de réparation électrique

1693EL



Profils

---

 1 year

Description produit

Constructed around a robust one-piece aluminum column, the Unior electric repair stand offers unparalleled stability while concealing all wires within, ensuring a clutter-free workspace for efficient bike maintenance. It


effortlessly lifts bikes up to 70kg to the desired height, ensuring optimal ergonomic conditions for every technician and every repair task. Endless height adjust makes lowering or lifting the bike with the push of a button a breeze, while automatic stopping system ensuring precise positioning. With knob adjustable travel limiters, users can customize the stand's range, while a built-in safety mechanism safeguards both technician and bicycle. With the versatile two-way control system, technician can choose between operating the stand via control panel or foot pedal, based individual preferences and needs. Additionally, an integrated adjustable LED light ensures consistent illumination, regardless of environmental lighting conditions. Built to endure, Unor Electric Repair stand is designed for longevity, requiring minimal maintenance and offers hassle free operation for years to come. Designed to be fully user serviceable, backed up with readily available spare parts and repair instructions.

### Caractéristiques :

- Main electricity supply cable discreetly routed from the top, eliminating workspace obstruction.
- Câbles cachés
- Système de réglage en hauteur sans fin
- Operable via intuitive control panel or convenient foot pedal.
- Automatic stopping system with unloading function for enhanced safety.
- Adjustable travel limiters are controlled by knob on the panel, with memory function for added convenience.
- Display of current load ensures optimal performance.
- Two USB ports (A and C) for convenient device charging and optional Wi-Fi connectivity.
- Self-diagnosing function.
- Mâchoire anti dérapante
- Équipé de la pince de réparation Master 1693.1M
- Integrated LED light provides optimal illumination in any environment.
- Aluminum main column.
- Easily mountable directly to the floor or heavy-duty metal fixed plate.
- Grande plaque fixe robuste avec fonction de nivellement du sol
- Minimal assembly required. Stand needs to be fixed to the floor or plate and control panel attached.

### Caractéristiques techniques :

- Load capacity: 700N (70kg)
- Maximum height: 1750 mm
- Power Requirements: 0,32kW
- Operating Voltage: 24V DC
- Input: 90V-260V; 47-63 Hz
- Movement speed: 5 m/min
- Indice de protection IP30: utilisation à l'intérieur uniquement
- conforme CE



Nom du produit	SKU	Article	Dimensions	Quantité
Stand de réparation électrique	629760	1693EL		2
Electric repair stand 2.0 without plate		1693EL1	90 - 260 V	1
Plaque fixe pour 1693EL		1693EL.1	740x740x12	1

\* Les images des produits ne sont pas contractuelles. Toutes les dimensions sont en mm, les poids en grammes.

### Utilisation (pictures)



### Photo (pictures)



## Accessories



Plaque fixe pour 1693EL



Le support de ordinateur pour 1693EL



Plateu a outils retractable pour 1693EL



Fixed plate for two electric repair stands

## Related products



Electric repair stand 2.0 without plate