

# Magnetic sticker for 266

1843MAGNET266










266

## Electronic torque wrench



- Target torque warning: Buzzer + 12 LED lights
- Operation Mode: Peak hold / Track
- Unit Selection: N-m, in-lb, ft-lb, kg-cm
- Head Type: Interchangeable Head
- Gear Teeth: 52
- Battery: AA x 2 pcs (not included)
- Data memory size: 250 inputs
- 10 preset torque settings
- Operating Temperature: -10°C~60°C
- Storage Temperature: -20°C~70°C
- Humidity: Up to 90 % non-condensing
- Warranty: 10.000 cycle / one year
- Online calibrations
- Electromagnetic compatibility certificate



							
266 (627576)	1/2"	410 mm	CW: +/-2% CCW: +/-3%	max.  135 N-m 99.5 ft-lb 1195 in-lb 1378 kg-cm	6.8~135 N-m 5~99.5 ft-lb 60~1195 in-lb 69~1378 kg-cm	0.1 N-m 0.1 ft-lb 1 in-lb 1 kg-cm	✓

## Profielen



[\(/be/support/warranty\).](#)





628169	EN (10-200Nm)	69
628170	EN (6,8-135Nm)	71
628165	EN (1,5-30Nm)	68
628166	SI (10-200Nm)	68
628167	SI (1,5-30Nm)	72

## Retail verpakking



- 628168
- 628169
- 628170
- 628165
- 628166
- 628167

## Transport verpakking



- 628168
- 628169
- 628170
- 628165
- 628166
- 628167