

Electric repair stand 2.0 without plate

1693EL1



Profili



Atributi proizvoda

Constructed around a robust one-piece aluminum column, the Unior electric repair stand offers unparalleled stability while concealing all wires within, ensuring a clutter-free workspace for efficient bike maintenance. It

effortlessly lifts bikes up to 70kg to the desired height, ensuring optimal ergonomic conditions for every technician and every repair task. Endless height adjust makes lowering or lifting the bike with the push of a button a breeze, while automatic stopping system ensuring precise positioning. With knob adjustable travel limiters, users can customize the stand's range, while a built-in safety mechanism safeguards both technician and bicycle. With the versatile two-way control system, technician can choose between operating the stand via control panel or foot pedal, based individual preferences and needs. Additionally, an integrated adjustable LED light ensures consistent illumination, regardless of environmental lightning conditions. Built to endure, Unor Electric Repair stand is designed for longevity, requiring minimal maintenance and offers hassle free operation for years to come. Designed to be fully user serviceable, backed up with readily available spare parts and repair instructions.

Features:

- Main electricity supply cable discreetly routed from the top, eliminating workspace obstruction.
- Hidden wiring for a sleek and professional appearance.
- Endless height adjustment for unparalleled versatility.
- Operable via intuitive control panel or convenient foot pedal.
- Automatic stopping system with unloading function for enhanced safety.
- Adjustable travel limiters are controlled by knob on the panel, with memory function for added convenience.
- Display of current load ensures optimal performance.
- Two USB ports (A and C) for convenient device charging and optional Wi-Fi connectivity.
- Self-diagnosing function.
- Anti-slip clamp interface ensures secure bike positioning.
- Equipped with Master shop repair clamp 1693.1M
- Integrated LED light provides optimal illumination in any environment.
- Aluminum main column.
- Easily mountable directly to the floor or heavy-duty metal fixed plate.
- Minimal assembly required. Stand needs to be fixed to the floor or plate and control panneal attached.

Technical specifications:

Load capacity: 700N (70kg)

Maximum height: 1750 mm

Power Requirements: 0,32kW


Operating Voltage: 24V DC

Input: 90V-260V; 47-63 Hz

Movement speed: 5 m/min

IP rating: IP30 – inside use only

CE compliant



	<i>2</i>	L	Н	H1 max	В	H1 min	
629761	90 - 260 V	361	2074	1795	324	240	45000

^{*} Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Accessories



Fixed plate for 1693EL



Laptop holder with foldable arm for 1693EL



Tool tray with foldable arm for 1693EL

Related products



Electric repair stand 2.0