

Electric repair stand 2.0 without plate

1693EL1

NEW



프로파일

 1 year

제품 특징

Constructed around a robust one-piece aluminum column, the Unior electric repair stand offers unparalleled stability while concealing all wires within, ensuring a clutter-free workspace for efficient bike maintenance. It


effortlessly lifts bikes up to 70kg to the desired height, ensuring optimal ergonomic conditions for every technician and every repair task. Endless height adjust makes lowering or lifting the bike with the push of a button a breeze, while automatic stopping system ensuring precise positioning. With knob adjustable travel limiters, users can customize the stand's range, while a built-in safety mechanism safeguards both technician and bicycle. With the versatile two-way control system, technician can choose between operating the stand via control panel or foot pedal, based individual preferences and needs. Additionally, an integrated adjustable LED light ensures consistent illumination, regardless of environmental lighting conditions. Built to endure, Unor Electric Repair stand is designed for longevity, requiring minimal maintenance and offers hassle free operation for years to come. Designed to be fully user serviceable, backed up with readily available spare parts and repair instructions.

특징:

- Main electricity supply cable discreetly routed from the top, eliminating workspace obstruction.
- 히든 와이어 처리
- 높이 조절 제한 없음
- Operable via intuitive control panel or convenient foot pedal.
- Automatic stopping system with unloading function for enhanced safety.
- Adjustable travel limiters are controlled by knob on the panel, with memory function for added convenience.
- Display of current load ensures optimal performance.
- Two USB ports (A and C) for convenient device charging and optional Wi-Fi connectivity.
- Self-diagnosing function.
- 미끄럼 방지 처리된 클램프 표면
- 1693.1M 마스터 샵 리페어 클램프 장착
- Integrated LED light provides optimal illumination in any environment.
- Aluminum main column.
- Easily mountable directly to the floor or heavy-duty metal fixed plate.
- Minimal assembly required. Stand needs to be fixed to the floor or plate and control panel attached.

기술 사양:

- Load capacity: 700N (70kg)
- Maximum height: 1750 mm
- Power Requirements: 0,32kW
- Operating Voltage: 24V DC
- Input: 90V-260V; 47-63 Hz
- Movement speed: 5 m/min
- IP 등급: IP30 – 실내 사용만 가능
- CE compliant



Barcode	Voltage	L	H	H1 max	B	H1 min	Weight
629761	90 - 260 V	361	2074	1795	324	240	45000

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

액세서리



1693EL용 고정 플레이트



1693EL용 접이식 랩탑 홀더



1693EL용 접이식 툴 트레이

관련 제품



전자식 리페어 스탠드