

# Electric repair stand 1.0 110V

Hidden

1693EL-110



Profiles

---

 **1 year**

Product features


Designed and developed for technicians to work smarter, not harder. The stand is constructed around heavy-duty one-piece aluminum column, which gives a great stability and at the same time holds all wires on the inside, so there's nothing in a way when working on a bike. It is strong enough to lift even the heaviest bicycles to the desired height with ease, so the bicycle is always in the most ergonomic position to work on. Electric repair stand is not just powerful, but also smart. It features endless height adjust, but it can also lift or descend a bike automatically with a push of a button. It also stops on its own when bike reaches the ground. Thanks to the travel adjust limiters; you can limit its travel, so it always stops at the desired height. Build in safety system keeps the technician and the bicycle on the stand safe and makes sure nothing goes wrong.




### Features:

- Automatic stopping system with a build in safety feature to keep technician and bicycle on the stand safe
- Endless height adjustment for unparalleled versatility.
- Travel adjust limiters
- Main electricity supply cable coming in from the top of the stand, so nothing is in the work area
- Hidden wiring for a sleek and professional appearance.
- Two USB A charging port
- Equipped with Master shop repair clamp 1693.1M
- Anti-slip clamp interface ensures secure bike positioning.
- Main column made of steel and bolted together creating a super rigid frame
- Secures directly to the floor or on a heavy-duty metal fixed plate
- Optional heavy-duty large fixed plate with floor leveling function
- No assembly needed, just fix it in place, plug in the electricity and start working

### Technical specifications:


- Measurement: W750xL750xH2072 mm
- Weight: 106 kg (with a steel fixed plate)
- Maximum height: 1780 mm
- Load capacity: 400N (40kg)
- Power: 0,25 kW
- Steering voltage: 5 V
- Input: 100-130 V; 60 Hz
- Movement speed: 3.3 m/min
- IP rating: IP30 – inside use only
- Noise level: 55 dB
- CE compliant



		L	H	H1 max	B	H1 min	
628789	100 - 130 V	750	2078	1808	750	250	97000

\* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

## Usage (pictures)



## Accessories



Fixed plate for 1693EL



Laptop holder with foldable arm for 1693EL



Tool tray with foldable arm for 1693EL



Frame mount tablet holder for 1693EL



Height extension kit for Electric repair stand 1.0



Clamping bracket with handle for clamp for 1693EL

## Related products



Electric repair stand 2.0



Electric repair stand 2.0 without plate