


Bearing service tool tray

1600SOS20-US



Profielen



Product attributen

- Installation kit includes spindle with two threaded handles, adaptors for following standard bearings: 608, 1526, 6000, 6001, 6802, 6803, 6804, 6805, 6900, 6901, 6902, 6903, R6, 28x17 (Hope), BB30, all Press-fit standards and two different sized plastic coated adaptors, to protect carbon surfaces during bearing installation.
- One of the threaded handles includes a quick release system for quick and easy use.
- Removal kit includes heavy duty slide hammer with adaptors that support bearing removal with inner bearing dimensions 6.5-8,10-12, 12-15, 17-20, 22-28, 30-36mm.
- All parts come arranged in a cut-out foam trays, that fits our Europlus, Eurovision, Eurostyle and Hercules trolleys

Productnaam	SKU	Artikel	Afmetingen	Hoeveelheid
Bearing service tool tray	629063	1600SOS20-US		30
Bearing press adaptor		1721.1	30 x 42 - BB30 (2x), 24 x 41 - BB86/92 (2x), 22 x 41 (2x), 10 x 26 - 6000, 10 x 22 - 6900, 12 x 28 - 6001, 12 x 24 - 6901, 15 x 28 - 6902, 15 x 24 - 6802, 15 x 26 - 1526, 17 x 28 - 17286, 17 x 30 - 6903, 17 x 26 - 6803, 20 x 32 - 6804, 25 x 37 - 6805, 9.5 x 22.2 (3/8" x 7/8") - R6 (2x), 8 x 22 - 608, DUB 29x42 (2x)	18
Bearing press protector		1721.2	,	2
Quick slide handle for 1721		1721.3		1
Handle with threaded rod for bearing press kit 1721		1721.4		1
Arm voor 689/5BI		689.1/5	6,5 - 8, 10 - 12, 12 - 15, 17 - 20, 22 - 28, 30 - 36	6
Blade with handle for 689/5BI-US		689.2/5BI-US		1
Tool tray for 1600SOS20		vl.1600SOS20	564x364x30	1

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Gebruik (Afbeeldingen)

